



Studio sound comes home

Featuring a Carbon Dome™ tweeter in a solid-body housing and a decoupled Continuum™ midrange, the 700 Series’ flagship floorstander brings studio-quality sound to your home audio set up. The speaker relays textural details with goosebump-inducing accuracy, making even largescale recordings sound stunningly lifelike.

Technical Specifications

Description	3-way vented-box system
Technical features	Decoupled Carbon Dome™ tweeter Solid Body Tweeter on top Continuum™ cone FST™ midrange Decoupled midrange Aerofoil™ Profile bass cones Flowport™
Drive units	1x ø25mm (1 in) Decoupled Carbon Dome high-frequency 1x ø150mm (6 in) Continuum cone FST midrange 3x ø165mm (6.5 in) Aerofoil Profile bass
Frequency range (-6dB)	-6dB at 28Hz and 33kHz
Frequency Response -3dB	45Hz - 28kHz ±3dB
Sensitivity	90dB spl (2.83V _{RMS} , 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 86Hz - 28kHz <0.5% 110Hz - 20kHz
Nominal impedance	8Ω (minimum 3.1Ω)
Recommended amplifier power	30W - 300W into 8Ω on unclipped programme
Dimensions	Height: 994mm (39 in) cabinet only 1087mm (42.8 in) including tweeter and plinth Width: 200mm (7.9 in) cabinet only 366mm (14.4 in) including plinth Depth: 337mm (13.3 in) cabinet only 364mm (14.3 in) including grille and terminals 452mm (17.8 in) including plinth
Net weight	29.5kg (65 lb)
Finishes	Cabinet: Rosenut Gloss Black Satin White Grille: Black Grey (Satin White only)