Bowers & Wilkins

700 Series 2
707 S2

Studio sound comes home

Small speaker, big sound. Ideal for smaller rooms, and designed for use on bookshelf or stand, the 707 produces tremendous highs and depths for a compact unit. Its two-way design and advanced drive units make for a sound that's clear, powerful and remarkably cohesive.

Technical Specifications

Description	2-way vented-box system
Technical features	Decoupled Carbon Dome™ tweeter Continuum™ cone bass/midrange Flowport™
Drive units	1x ø25mm (1 in) Decoupled Carbon Dome high-frequency 1x ø130mm (5 in) Continuum cone bass/midrange
Frequency range (-6dB)	-6dB at 45Hz and 33kHz
Frequency Response -3dB	50Hz - 28kHz ±3dB
Sensitivity	84dB spl (2.83V_{RMS}, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 110Hz - 22kHz
Nominal impedance	8Ω (minimum 4.0Ω)
Recommended amplifier power	30W - 100W into 8Ω on unclipped programme
Dimensions	Height: 280mm (11 in) Width: 165mm (6.5 in) Depth: 260mm (10.2 in) cabinet only 276mm (10.9 in) including grille and terminals
Net weight	6.0kg (13.2 lb)
Finishes	Cabinet: Rosenut Gloss Black Satin White Grille: Black Grey (Satin White only)

Bowers & Wilkins

www.bowers-wilkins.com

Carbon Dome, Continuum, FST and Flowport are trademarks of B&W Group Ltd.

Copyright © B&W Group Ltd. E&OE

This information is intended as a guide only and reflects the current specification at the time of print. We reserve the right to make changes to the specifications