Bowers & Wilkins

700 Series 2
HTM72 S2

Studio sound comes home

This high performance two-way centre speaker is a great choice for home cinema set-ups in smaller rooms, where space is at a premium. Partner it up with the more compact 700 Series speakers, such as the 706 or the 704.

Technical Specifications

Description	2-way vented-box system
Technical features	Decoupled Carbon Dome™ tweeter Continuum™ cone bass/midrange Flowport™
Drive units	1x ø25mm (1 in) Decoupled Carbon Dome high-frequency 2x ø130mm (5 in) Continuum cone bass / midrange
Frequency range (-6dB)	-6dB at 48Hz and 33kHz
Frequency Response -3dB	70Hz - 28kHz ±3dB
Sensitivity	87dB spl (2.83V_{RMS}, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 100Hz - 22kHz <0.5% 200Hz - 22kHz
Nominal impedance	8Ω (minimum 4.3Ω)
Recommended amplifier power	30W - 120W into 8Ω on unclipped programme
Dimensions	Height: 166.5mm (6.6 in) Width: 480mm (18.9 in) Depth: 260mm (10.2 in) cabinet only 275mm (10.8 in) including grille and terminals
Net weight	9.11kg (20.1 lb)
Finishes	Cabinet: Rosenut Gloss Black Satin White Grille: Black Grey (Satin White only)

Bowers & Wilkins

www.bowers-wilkins.com

Carbon Dome, Continuum, FST and Flowport are trademarks of B&W Group Ltd.

Copyright © B&W Group Ltd. E&OE

This information is intended as a guide only and reflects the current specification at the time of print. We reserve the right to make changes to the specifications