SPECIFICATIONS Display Projection System DLP DMD type 0.47" Native Resolution 4K UHD (3840 x 2160) Resolution **Brightness** 3000 ANSI Lumens Contrast Ratio** 30,000:1 (Dynamic Iris) Display Color 30,000:1 (Dynamic Iris) Aspect Ratio Native 16:9 (6 aspect ratio selectable) Light Source Light Source life*** Normal 4000 hours Eco 10000 hours SmartEco 15000 hours **Optical** 1.13 - 1.47 (100" @ 8.2 ft) Throw Ratio Zoom Ratio 1.3X Keystone Correction ID, (Auto) Vertical ± 30 degrees Projection Offset 100% Vertical +10% LenShift 40"~200"/30"~300" Projection Size (Clear Focus / Maximum) Audio Built-in Speaker 5W x 2 (Chamber) **Picture** Picture Mode Bright / Living Room / Cinema/ Sports / Silence / (3D)* / User I / HDR / HLG Color Wheel Segment 4 segment (RGBW) 2D: 96Hz; 100Hz; 120Hz Color Wheel Speed 3D: 120Hz Special Feature Security Security Bar, Kensington lock Feature HDR10, HLG, 3D, CinemaMaster Video + (Motion Enhancer 4K, Pixel Enhancer 4K), CinemaMaster Audio + 2, Auto Keystone Compatibility VGA (640 \times 480) to 4K UHD (3840 \times 2160) Resolution Support 15K-135KHz Horizontal Frequency Vertical Scan Rate 23-120Hz 720p 50/60Hz, 1080i 50/60Hz, 1080p 24/25/30/50/60Hz, 2160p **HDTV** Compatibility 23/24/25/30/60Hz Power Power Max 350W. Normal 340W, Eco 280W Consumption(Max/Normal/Eco) 0.5W Max. at 100 ~ 240VAC Standby Power Consumption VAC 100 ~ 240 (50/60Hz) Power Supply Dimension and Weight Product Dimensions (WxHxD) $14.96 \times 5 \times 10.35$ in / $380 \times 127 \times 263$ mm Product Weight 9.3 lb/ 4.2 kg Operation Condition Noise Level(Normal/Eco) 30/28dBA (Silence mode) Operating Temperature 0~40 degrees (Celsius) Accessories Accessories (Standard) Remote Control - RCV017 w/ Battery x I (5J.JKC06.001) Power Cord (by region) x I(3m) User Manual CD (27L)

TK850

Home Entertainment















KEY FEATURES

- True 4K UHD (3840 x 2160) 8.3M pixel resolution
- Vivid colors and high brightness cut through living room ambient light
- Sport Mode powered by 98% Rec.709 coverage with optimized RGBW color wheel
- HDR-PRO™ projector-optimized HDR10 and HLG for live 4K broadcasting content
- High contrast 30,000: I with dynamic Iris for sharpness
- Enables a 100" picture from 8.2 feet with short throw projection
- Easy to adjust image with vertical lens shift and auto vertical keystone
- Immersive 3D experience with resolution up to 1920x1080
- Supports up to 15,000 hours lamp life
- Customizable to your personal needs with ISFccc® Certificated control
- HDMI for your Apple TV 4K, Xbox One X and PS4 Pro
- Motion Enhancer to eliminate motion blur and noise in fast-motion video content

DIMENSIONS







- I. HDMI x 2(2.0b, HDCP2.2)
- 2. USB TypeA (5V/2.5A power)
- 3. USB TypeA (Media Reader, FW download)
- 4. USB Type min B (FW download, service)
- 5. Audio out (mini jack)
- 6. Audio out (S/PDIF) (Only support 2-channel audio)
- 7. RS232 In (D-sub 9pin, male)
- 8. DC 12V Trigger (3.5mm Jack)

*In 3D Mode: Resolution is 1920×1080 in 3D Mode. **The Contrast is measured by Full On Full Off standard.
***Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without not





Accessories (Optional)

BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands, and other trademark featured or referred to in this material are the property of their respective trademark holders. Specifications subject to change without notice.

Quick Start Guide (21L)

Spare Lamp Kit (5].JKC05.001)

Warranty Card

3D Glasses